



# Nokia ONT XS-010X-Q

## XGS-PON SFU ONT

The Nokia Optical Network Terminal (ONT) XS-010X-Q that has one 1/10 Gigabit Ethernet (GigE) is part of the industry-leading Nokia ONT product family and is compatible with the Nokia 7360 ISAM fiber to the x (FTTx) product line. It is designed to deliver triple play services in a fiber to the home (FTTH) environment to single family units (SFUs) where an Ethernet port is required.

The Nokia ONT terminates the 10 G symmetrical Passive Optical Network (XGS-PON) fiber interface that is compliant with a Full Service Access Network (FSAN).

The Nokia ONT XS-010X-Q is designed for residential customer requirements and offers data services to the subscriber through FTTH or fiber to the premises (FTTP) applications. The Nokia ONT XS-010X-Q is an ONT suitable for indoor deployments and is compliant with ITU-T G.9807.1 supporting a line rate of 10 Gb/s upstream and 10 Gb/s downstream. With XGS-PON as the uplink interface, the XS-010X-Q is also compliant with the standard optical network unit (ONU) management and control interface (OMCI) definition. The XS-010X-Q can be managed from a remote site using application management services (AMS) and supports the full range of fault, configuration, accounting, performance, and security (FCAPS) functions.



- Per subscriber, per service bandwidth control
- Remotely managed by the Nokia 5520 AMS
- IP video with multistage Internet Group Management Protocol (IGMP) v2/v3 for channel change
- Supports received signal strength indication (RSSI) for lean operations and remote troubleshooting

## Features

- WAN: XGS-PON, SC/APC
- LAN: 1x100M/1G/2.5G/5G/10G BASE-T RJ-45, auto negotiating supported
- ITU-T G.9807.1, G.988 compliant
- Wire speed data transfer

## Benefits

- Enables operators to capture new revenues with services that require 10 Gb/s symmetrical
- Eco-sustainability is in line with “green” tendencies: low power consumption

- IGMP snooping monitors the member joining and leaving activities at the Ethernet port, then selectively delivers the multicast streams
- Power supply with dying gasp functionality
- Advanced dynamic bandwidth management

## Technical specifications

### Physical

(Height, width and length dimensions)

- Height: 3.0 cm (1.18 in)
- Width: 13.5 cm (5.31 in)
- Length: 13.5 cm (5.31 in)
- Weight: 0.366kg (0.81 lb)

### Installation

- Desktop or wall mounting

### Power requirements

- 12 VDC /1A
- Power consumption: <8.6 W

### Operating environment

- Temperature (ambient): -5°C to 45°C (23°F to 113°F)
- Relative humidity: 5% to 95%, non-condensing

### XGS PON uplinks

- Wavelength: 1260 nm–1280 nm upstream; 1575 nm–1580 nm downstream
- G.9807.1 XGS PON standards compliant: 4 dBm ~ 9 dBm launch power; -28 dBm ~ -9 dBm for receiving
- SC/APC connector
- 10 G burst mode upstream transmitter
- 10 G downstream receiver
- G.9807.1-compliant 10 GPON Encapsulation Method (XGEM) framing
- Flexible mapping between XGEM ports and T-CONT
- Advanced Encryption Standard (AES) 128

- Forward error correction (FEC)
- Activation with automatic discovered serial number and password

### Ethernet interfaces

- One LAN 100 M/1 G/2.5 G/5 G/10 G Base-T interface with RJ-45 connector
- Ethernet port auto-negotiation or manual configuration with medium dependent interface/ medium dependent interface crossover (MDI/ MDIX)
- Virtual switch based on IEEE 802.1Q virtual LAN(VLAN)
- VLAN stacking (Q-in-Q) and VLAN translation
- CoS based on VLAN ID, 802.1p bit
- IGMP v2/v3 snooping

### Operations, administration, and maintenance (OA&M)

- Standard compliant OMCI (the embedded operations channel) interface as defined by ITU-T G.984.4 and ITU-T G.988
- Supports local WebGUI for the ONU authentication password configuration from the LAN side
- Management information base (MIB) manipulation over OMCI with create, delete, set, get and get next commands
- Alarm reporting and performance monitoring
- Remote software image download over OMCI, as well as activation and rebooting
- Supports subscriber line identifier (SLID) using WebGUI

### LEDs

- Power
- PON
- Alarm
- Data

## RJ-45 LEDs

- Mode/Status
- Link/Carrier

## Safety and electromagnetic interference (EMI)

- FCC compliant
- UL 60950-1
- CE Mark

## About Nokia

We create the technology to connect the world. Only Nokia offers a comprehensive portfolio of network equipment, software, services and licensing opportunities across the globe. With our commitment to innovation, driven by the award-winning Nokia Bell Labs, we are a leader in the development and deployment of 5G networks.

Our communications service provider customers support more than 6.4 billion subscriptions with our radio networks, and our enterprise customers have deployed over 1,300 industrial networks worldwide. Adhering to the highest ethical standards, we transform how people live, work and communicate. For our latest updates, please visit us online [www.nokia.com](http://www.nokia.com) and follow us on Twitter [@nokia](https://twitter.com/nokia).

Nokia is a registered trademark of Nokia Corporation. Other product and company names mentioned herein may be trademarks or trade names of their respective owners.

© 2020 Nokia

Nokia OYJ  
Karakaari 7  
02610 Espoo  
Finland  
Tel. +358 (0) 10 44 88 000

Document code: SR2007045685EN (July) CID207690