

Network products

For more information, visit:
www.al-enterprise.com

Alcatel•Lucent

OmniAccess®
Stellar

Wi-Fi 7 Outdoor OmniAccess Stellar 1570

Outdoor mid-range Wi-Fi 7 access point for harsh environments

- 9.328 Gbps • 768 clients • 48 SSID • Tri Radio, 6 GHz 2x2:2, 5 GHz 2x2:2 and 2.4 GHz 2x2:2
- USB-C • Scanning radio • USB 2.0 • 1x10GbE • 1x1GbE
- MLO • 320MHz • 4K-QAM • DL and UL MU-MIMO
- Max power: 50W • WPA3
- Temp: -40°C to 65°C
- BLE/Zigbee integrated • TPM 2.0
- PoE powered 802.3at/bt • IP67
- Retrocompatible with previous standards



Wi-Fi 7 Indoor OmniAccess Stellar 1540

Indoor high-range Wi-Fi 7 access point

- 18.67 Gbps • 1536 clients per AP • 16 SSID per Radio, 48 SSID per AP
- Tri Radio, 6 GHz 4x4:4, 5 GHz 4x4:4 and 2.4 GHz 4x4:4
- USB 2.0 with USB-C port • Scanning radio • BLE/Zigbee radio
- 1x10GbE • 1x10GbE • 1x10GbE • 5FP/5FP+
- MLO • OFDMA • DL and UL MU-MIMO
- 320MHz • 4K-QAM • WPA3 • Temp: 0°C to 45°C
- TPM 2.0 • PoE powered 802.3bt redundancy
- PoE powered 802.3at load balancing with the two Ethernet ports
- Retrocompatible with previous standards



Wi-Fi 7 Indoor OmniAccess Stellar 1511

Indoor entry range Wi-Fi 7 access point

- 9.328 Gbps • 768 clients • 48 SSID
- Tri Radio, 6 GHz 2x2:2, 5 GHz 2x2:2 and 2.4 GHz 2x2:2 • USB-C • USB 2.0
- 1x 5GbE • MLO • 320MHz
- DL and UL MU-MIMO • WPA3
- Temp: 0°C to 50°C • TPM 2.0
- BLE/Zigbee integrated
- PoE powered 802.3at • Max power: 23.4W
- Retrocompatible with previous standards



Wi-Fi 7 Indoor OmniAccess Stellar 1501S

Indoor entry range Wi-Fi 7 access point for small and medium enterprises

- 3.5 Gbps • 256 clients • 16 SSID
- Dual Radio, 2.4GHz 2x2 and 5GHz 2x2
- DC 48V Jack • 1x2.5GbE • MLO
- OFDMA • DL and UL MU-MIMO
- 320MHz • 4K-QAM • WPA3
- Max power: 13W
- PoE IEEE 802.3at compliant
- Retrocompatible with previous standards



Wi-Fi 6E Indoor OmniAccess Stellar 1451

Indoor high-end Wi-Fi 6E access point for increasing IoT needs

- 10 Gbps • 1536 clients • 48 SSID
- Tri radio 2.4GHz 4x4, 5GHz 8x8 and 6GHz 4x4
- Scanning radio • USB 3.0 • 10GE+10GE
- DL and UL MU-MIMO • WPA3 • Target Wake Time
- Temp: 0°C to 45°C • Max power: 49W
- Retrocompatible with previous standards
- PoE powered 802.3bt • BLE/Zigbee integrated



Wi-Fi 6E Indoor OmniAccess Stellar 1431

Indoor Wi-Fi 6E access point that provides high-efficiency and high-performance for high client density environments.

- 4.2 Gbps • 512 clients • 16 SSID • Tri Radio, 6 GHz 2x2:2, 5 GHz 2x2:2 and 2.4 GHz 2x2:2 • Max power: 34W
- USB 3.0 • 2.5GE + 2.5GE • DL and UL MU-MIMO • WPA3
- Target Wake Time • Temp: 0°C to 45°C
- Retrocompatible with previous standards
- PoE powered 802.3bt • BLE/Zigbee integrated



Wi-Fi 6 Outdoor OmniAccess Stellar 1360

Ruggedized Wi-Fi 6 access point for outdoor high-density environments

- 3 Gbps • 1024 clients • 16 SSID
- 2.23 Kg • DPI • IP67 rated
- 4 radios - 1 dedicated to scanning
- WPA3 • DL and UL MU-MIMO
- Target Wake Time
- Temp: -40°C to 65°C
- Retrocompatible with previous standards
- Max power: 70W
- PoE powered 802.3bt/at
- BLE integrated



Wi-Fi 6 Indoor OmniAccess Stellar 1351

Outstanding bandwidth and speed for very demanding environments

- 10 Gbps • 1536 clients • 24 SSID • 1200 g
- DPI • WPA3 • Tri radio 2.4GHz and Dual 5GHz
- 1 radio dedicated to scanning
- DL and UL MU-MIMO • Target Wake Time
- Temp: 0°C to 45°C • Max power: 60W
- Retrocompatible with previous standards
- PoE powered 802.3bt • BLE/Zigbee integrated



Wi-Fi 6 Indoor OmniAccess Stellar 1331

Wi-Fi 6 mid-range access point for larger enterprises with intensive Wi-Fi usage

- 3.55 Gbps • 1024 clients • 32 SSID • TWT
- 985 g • DPI • Dual Radio DL & UL MU-MIMO
- 1 radio dedicated to scanning
- Temp: 0°C to 45°C • Max power: 23W
- PoE powered 802.3bt/at
- BLE/Zigbee integrated
- Retrocompatible with previous standards



Wi-Fi 6 Indoor OmniAccess Stellar 1301

Wi-Fi 6 access point, basic entry-level for indoor, ideal for small and medium enterprises

- 1.77 Gbps • 512 clients • 16 SSID
- 574 g • DPI • Dual radio • WPA3
- DL and UL MU-MIMO
- Target Wake Time • Temp: 0°C to 45°C
- Retrocompatible with previous standards
- Max power: 13.1 W
- PoE powered 802.3af



Wi-Fi 6 Indoor OmniAccess Stellar 1301H

Wi-Fi 6 indoor designed for vertical industries and teleworkers

- 1.77 Gbps • 1024 clients • 32 SSID • 320 g
- DPI • Dual Radio • WPA3 • DL & UL MU-MIMO
- TWT • Temp: 0°C to 45°C
- Max power: 12.7 W
- PoE powered 802.3at/af
- BLE/Zigbee integrated
- Retrocompatible with previous standards



Distributed Wi-Fi Control Architecture

Alcatel-Lucent OmniAccess Stellar products embed WLAN control in access points (APs) and eliminating the need for physical centralised controllers.

Alcatel-Lucent smart and advanced APs are managed as a single system or cluster, in a distributed and coordinated manner. Distributed architecture from Alcatel-Lucent delivers the best performance and scalability, and ensures high availability, with operational simplicity and low Total Cost of Ownership (TCO).

- Integrated WLAN controller
- Coordinated intelligence
- Lower CAPEX & OPEX
- Improved resiliency
- No traffic bottleneck and decreased latency
- Better scalability

OmniFabric: Network fabric for enhanced security

A multi-technology autonomous fabric ensuring end-to-end security

- Supports SPB, MPLS and EVPN within a single operating system (AOS) ensuring superior flexibility and performance.
- Offers embedded, automated IoT device detection and segmentation.
- Advanced automation features streamline network operations, reduce manual intervention and minimize human errors.
- Compatible with environments where equipment from various vendors coexist, eliminating vendor lock-in
- Optimized Total Cost of Ownership (TCO)
- Available for both indoor and outdoor/harsh environments.

Shortest Path Bridging (SPB)

Upgraded Ethernet network provisioning: SPB delivers traffic on the shortest path available, enabling virtualization and real-time apps.

It optimizes network performances and minimize downtime when adding, removing or replacing network devices — no matter the underlying physical architectural design, whether it is a virtual chassis, a pod, a mesh or a spine and leaf configuration.

- Dynamic network topology
- Less complex operations
- Create a multi-path fabric for traffic distribution
- Automatic configuration
- Plug-and-play capabilities
- Save time
- Optimize available bandwidth

OmniSwitch®

Premium access OmniSwitch 6870

Advanced 24/48 ports 1G/Multi-gig and 25G switches for campus and Data Center networking

- All Multi-gig ports on PoE models, comprehensive 2.5G/5G/10G models to select
- 802.3bt PoE up to 95W per port and 3.3 kW PoE budget • Flexible PSU Load-Sharing PoE
- PoE and non-PoE models can stack together • Various uplink speed up to 200G
- OmniFabric ready • 256-bit MACsec on all ports • Telemetry • SPB • VxLAN
- Virtual chassis • QoS • IPv4/v6 • VRF • Advanced routing • Multicast • UNP



Premium access OmniSwitch 6860E

Advanced 24/48 ports 1G/Multigig switch for campus and Data Center networking

- PoE+ and non-PoE models • Up to 75W PoE and 1.5 kW PoE budget
- VxLAN • SPB • OmniFabric • Virtual chassis • Automatic VLAN
- Context-based QoS • JTIC • IPv4/v6 • FIPS • VRF • Advanced routing
- Multicast • EAL-2/NDcPP • UNP • Smart analytics
- Application analytics • MACSec encryption



Advanced access OmniSwitch 6570M

Advanced 12/28 ports 1G/10G switch for Enterprise and Service Provider Networks

- Metro Ethernet Services enabled
- Virtual chassis • Automatic VLAN • Advanced QoS
- IPv4/v6 • Static/Dynamic routing • Multicast • UNP
- EAL-2/NDcPP • CE 3.0 certified • MACSec encryption



Advanced access OmniSwitch 6560/E

Cost-effective Layer 3 24/48 ports Multigig access switch for large IoT-based and Wi-Fi 6/7 networks

- 802.3bt PoE • PoE+ and non-PoE models • 2x20G virtual chassis ports
- Fiber SFP+ ports • Modular load-sharing power supplies
- Up to 95W/port • IoT profiling enablement • Advanced QoS
- IPv4/v6 • Static/Dynamic routing • UNP • MACSec encryption
- Automatic VLAN • Context-based QoS • Virtual chassis



Advanced access OmniSwitch 6370

Stackable 12/24/48 ports Gigabit and Multi-Gigabit access switch with 95W PoE for enterprise branch and IoT-ready networks

- PoE+ and non-PoE models • Multi-Gigabit (2.5G) PoE models with up to 95W per port • 10G SFP+ uplinks • Virtual chassis up to 8 units with ISSU • Perpetual and Fast PoE support across all PoE models • Up to 760W PoE budget (48-port models)
- Fanless 12/24-port models available • Zero Trust architecture • Secure Boot • Access Guardian • UNP • IoT device profiling and containment • Advanced QoS and ACLs • DoS protection • Static/Dynamic IPv4/v6 routing (advanced routing via SW license) • Zero-touch provisioning • WebView 2.0 • RESTful API • Designed for NDcPP certification



Value access OmniSwitch 6360

Advanced Layer 2+ 10/24/48 ports 1Gb for classroom, campus and small/branch enterprise

- PoE+ and non-PoE models • 10G SFP+ uplinks Static IPv4/v6 routing
- UNP • IoT enablement • Fanless (10/24 ports) • Virtual Chassis
- Perpetual/Fast PoE • Multigig/iPoE on P48X model



Advanced rugged industrial switch OmniSwitch 6865

Advanced Layer 3 fanless Ethernet switches designed to operate in the harshest industrial environments

- PoE+ and non-PoE models • SFP+ uplinks SPB Virtual chassis
- Temp: -40°C to 75°C • EAL-2/NDcPP • Advanced stacking and routing • VRF • Multicast • IPv4/v6 • JTIC • UNP
- Automatic VLAN • Advanced L3 • Fast / Perpetual
- High surge tolerance • 802.3bt PoE
- HPoE up to 75W/port • IoT enablement
- FIPS 140-2 • iFAB
- Certified for: DNV MIL Railway Electric substation TAA NEMA-T52



Rugged industrial edge switch OmniSwitch 6575

Advanced fanless Layer 3 industrial Ethernet switches delivering high-power PoE, precision timing, and secure automation for harsh, mission-critical environments

- Operating temperature: -40°C to +75°C • High shock, vibration, surge, and EMI/EMC tolerance • Fan-less, convection-cooled industrial design
- DIN rail, wall/panel, and 19" rack mounting • PoE+ and non-PoE models
- IEEE 802.3bt PoE up to 90W per port • Fast PoE and Perpetual PoE
- SFP+ uplinks • IEEE 1588v2 PTP, G.8275.1/2, and SyncE support
- Sub-microsecond / nanosecond-level time synchronization
- MACsec-256 • Dual redundant AC/DC power inputs
- Integrated alarm relay interfaces • Virtual Chassis
- SPB • Auto-Fabric and Zero Touch Provisioning
- Advanced Layer 3: VRF, Multicast, IPv4/IPv6 routing
- Certified for IEC 61850-3, EN 50155, IEEE 1613



Compact rugged industrial switch OmniSwitch 6465/6465T

Compact hardened fanless 6/12/28 ports Gigabit Ethernet switches for industrial applications

- PoE+ and non-PoE models • 802.3bt PoE
- HPoE up to 60W/port • Instant/continuous PoE
- Network automation • Virtual chassis
- High surge tolerance • DIN mountable
- MACSec encryption
- Zero touch provisioning
- IoT enablement
- Support IEEE 1588v2 PTP
- Disaster recovery
- Extended temperature ruggedized



Modular core switch OmniSwitch 9900

High-density chassis for core campus and Data Center networks

- 7 and 12 slot modular chassis
- 25.6 Tb/s aggregated switching capacity (with two OS9907-CFM2)
- Up to 10,800W of PoE budget
- Virtual chassis • VRF • Advanced routing
- MACSec • Multicast • IPv4/v6
- FIPS 140-2 Core network and / DC Fabric at 1 G/10G/25G/40G/100G
- Programmability: Python, RESTful API, OpenStack
- EAL-2/NDcPP • JTIC • SPB • UNP



Fixed core / spine switch OmniSwitch 6920

High-density 400G switch for data center core and Fabric architectures

- 1U fixed-form-factor switch • 32 x QSFP-DD ports supporting 400G Ethernet • Up to 12.8 Tb/s total bandwidth • Ultra-high-density switching for spine, super-spine, and border-leaf roles
- Fabric Data Center for AI, HPC • Microsoft Azure Local certified
- Layer 2 and Layer 3 switching • High-bandwidth east-west traffic handling • RoCEv2 and PFC • SPB • Multi-tenant Fabric and VPN service support • Advanced routing and VRF
- IPv4/IPv6 unicast and multicast
- Energy-efficient architecture
- Programmability: RESTful APIs, JSONXML, Python, CLI, SNMP, Zero-touch provisioning, SDN-ready



Stackable core switch OmniSwitch 6900

High-performance switch for core campus and Data Center networks

- 1U switches • Multiple fixed configurations of 1/10/25/40/100G ports • Virtual chassis
- Advanced routing • VRF • Multicast • IPv4/v6
- JTIC • ISSU • SPB • UNP • Programmability: SDN, OpenStack, Python, Rest API, SSH
- FIPS 140-2 • EAL-2/NDcPP • MACSec



SMB and Websmart access OmniSwitch Lite 2270/2370

Smart & Stackable 8/24/48 ports Gigabit Ethernet Switches for SMB and IoT-ready networks

- PoE+ and non-PoE models (2270) • All-PoE+ models (2370)
- 10G SFP+ uplinks on 2370 models • 1G SFP uplinks on 2270 models
- Virtual Chassis up to 8 units (2370) • Standalone (2270)
- Up to 760W PoE budget (OS2370L-P48X) • Up to 370W (2270/P48)
- Perpetual PoE and Fast PoE support
- Fanless models available (8-port variants)
- Static IPv4/v6 routing and RIP
- 802.1X / MAC Auth • Advanced QoS and ACLs
- Zero-touch provisioning
- IoT-ready: DHCP snooping, LPS, DoS protection
- LACP, MSTP/RSTP/PVST+ • Jumbo frames 9KB



SMB and Websmart access OmniSwitch 2260/2360

Cost Effective 8/24/48 ports stackable, websmart Gigabit Ethernet Switch

- Virtual chassis • Standalone • PoE+ and non-PoE models
- Static IPv4/v6 routing • Fiber SFP Ports
- Fanless (10/P10/24 ports)
- Perpetual/Fast PoE
- 802.1X/MAC Auth
- Advanced QoS and ACLs
- 10G SFP+ uplinks on "X" models



Alcatel-Lucent OmniVista® Network Management Platform

Unified LAN/WLAN management in flexible cloud or on-premises deployment


- Web-based user interface
- Multi-tenant support, multi-customer management
- Comprehensive analytics, proactive service assurance, and advanced network control through UPAM
- Intelligent QoE metrics, user and network behavior analytics and real-time alerting with Rainbow CPaaS
- AI-Enhanced Efficiency: Leverage AI-based analytics and intelligent chatbot assistance



Alcatel-Lucent Network Fleet Supervision

Network inventory & support visibility from a single platform

- Free of charge online tool
- Inventory management with OmniVista management systems
- Manual option to import serial numbers
- Service/support status, device lifecycle warranty, software version
- Assess and control your compliance (e.g. NIS2)



Alcatel-Lucent OmniVista® Network Advisor

Network Advisor is an AI-powered IT companion that eases network teams' daily operations

- Detect network issues • Simplify troubleshooting
- Accelerate security threat detection, reaction & mitigation
- Benchmark network performance
- Get alerts on possible provisioning errors and proposal on corrections
- Get a comprehensive picture of the health of the network



Plugin Video
Management
Systems

OmniSwitch VMS Plugin for Milestone solutions

Boost operational efficiency and improve video surveillance infrastructure security.

- It allows users to create, modify, and delete Alcatel-Lucent switches connected to cameras managed by the VMS
- Up to 70% of camera problems can be resolved remotely by the VMS operator
- Enhances the efficiency and responsiveness of the camera management system
- Enables you to view cameras connected to the switchboards and provide real-time status of the switches and ports
- Allows resetting of a camera and locking the MAC address to a port directly from the smart client



Network
as a Service

Network as a Service by Alcatel-Lucent

It is a new way for businesses to purchase network infrastructure—hardware, licenses, applications, and management tools—with agile life cycle services through subscriptions. This is a modular offer to meet your business needs.

- Reduce time to benefit • Quickly adapt to business needs
- Maximum agility and scalability
- Free up IT Staff with improved network operations
- Predictable costs for your network infrastructure
- All-inclusive Support Offer

Click for more details

Communications products

For more information, visit:
www.al-enterprise.com

Alcatel • Lucent



Mission-critical communications

Connected platforms - Hybrid Cloud

On-premises connected platform to cloud services (Private or Public SaaS)
Hybrid/IP/SIP/Digital connectivity

Communications Suite for SMB

OXO Connect • SMB business communications • Compact and small models
OXO Connect Evolution • 100% IP • Rainbow WebRTC Gateway included

Communications Suite for MLE

OmniPCX Enterprise Purple • Campus • Centralized multi-site
• Virtual or Appliance • Native encryption • Single Pair Ethernet

Purple on Demand • Subscription-based offering

• Based on the OmniPCX Enterprise Purple platform and its applications suite

OmniPCX Open Gateway

• REST full APIs platform for OmniPCX Enterprise Purple platform

OpenTouch® Session Border Controller

• SIP perimeter defense for MLE

Network Management System

OmniVista 8770 NMS • Modular network management

• Role-based delegation • VoIP reports

Click for more details




Rainbow Hybrid

- Unified communications for connected platforms (WebRTC gateway integrated or connected to the PBX)
- Multi-devices (Desktop, Web, iOS, Android) • One number service • Call transfer • Audio/video calls
- Team collaboration • Secure messaging • File sharing
- Video conferencing up to 49 on-screen participants • Meeting room equipment
- Integration with Microsoft 365® and Google Suite®
- SaaS connectors (Office suite, CRM, ERP, ITSM)

Rainbow Hybrid Services Plans:

Rainbow Hybrid comes with a subscription per user/month or year(s): Business, Enterprise, Enterprise Dial-in, Attendant and options (Connect, Room, Alert).

Details are available from your sales representative or Business Partner.



Click for more details

Private Cloud

Rainbow Edge

- For large enterprises that require their data to be hosted on their own instance – in a private cloud or on-premises



Click for more details

Purple on Demand

- Business communications as a Service (based on a subscription)
- Hosted or on-premises
- Based on the OmniPCX Enterprise Purple platform

UCaaS Public Cloud

Rainbow Hub

A complete cloud-based solution for all your communications needs.
Traffic via Business Partners.

All in one: telephony, collaboration and video conferencing

Multi-devices: single intuitive application available on PC, tablet and smartphone

Flexible: pay per user model with full scalability

Trusted: a sovereign cloud platform

Rainbow Hub Services Plans:

Rainbow Hub comes with a subscription per user/month or year(s): Voice Phone, Voice Business, Voice Enterprise, Voice Enterprise Dial-in, Voice Attendant and options (Connect, Room, Alert).

Details are available from your sales representative or Business Partner.

Click for more details



Security and Compliance

- ANSSI CSPN
- ISO 27001
- European GDPR
- HiPAA
- HDS
- ENS
- FERPA
- Encryption of communications and data

Per solution details on our public web site.

Click for more details



Applications

Contact Center - Attendant - Recording Customer interactions




Solutions for SMB

- **OmniTouch® Call Center Office** • Company greeting • Distribution • Reporting • Statistics
- **Built-in OXO Connect applications** • Greeting message • Automated attendant
- Attendant console • Voicemail • Smart call routing • Hospitality features
- **PIMphony** • Basic • Pro • Team • Attendant • Personal Communication Manager

Solutions for MLE

- **ALE Connect** • Omnichannel contact center (email, live chat, social media, and phone)
- Web-based Agent Desktop • Hybrid Cloud service with OmniTouch Contact Center SE
- **OmniTouch Contact Center SE** • Call supervision and distribution
- **Soft Panel Manager** • Contact Center statistics and business data display in real time
- **Visual Automated Attendant** • Automated 24/7 call routing and greeting
- **4059 Extended Edition Attendant Console** • Professional welcome PC application
- **OmniPCX RECORD Suite** • Call recording, video and screen capture

Click for more details



OmniPCX RECORD Suite

Industries Verticals

Education

- Empowering student success

Energy and Utilities

- Enabling smarter, safer and greener energy and utilities

Government

- Optimizing government efficiency and public safety

Healthcare

- Optimizing the care pathway

Hospitality

- Empowering staff digital services

Transportation

- From connected to smart transportation

Visual Notification Assistant

- Broadcast voice and text messages to phones and applications
- Manage situations including geolocation of Alcatel-Lucent phones and softphones
- **Dispatch Console** • Intelligent call processing for mission-critical communications
- **OmniPCX Open Gateway** • Integrate communications in your business application of choice
- **Remote Visual Assistance** • Digitizing and connecting field services for operational excellence

Rainbow Hospitality • Transforming hotel operations through better communication

Rainbow CPaaS • Connect real-time communications to your application ecosystem

Rainbow Alert • Priority-based messaging with persistent audio alerts

Rainbow Classroom • Recreate the physical classroom with real-time collaboration with or without an LMS

Rainbow Click-to-Connect • Chat, call with video from within any website


Alcatel-Lucent Developer and Solution Partners Program (DSPP)

Refer to the DSPP program for the development of unique applications on premises or in the Cloud with APIs: www.al-enterprise.com/en/partners/dspp


Click for more details



Visual Notification Assistant



Rainbow Click-to-Connect



Rainbow Alert



Dispatch Console



Rainbow Classroom



Remote Visual Assistance

Business application integrations

Connectors for the most popular SaaS applications:


- Microsoft Teams
- Microsoft Dynamics
- Zendesk
- Zoho
- Jadu
- Pipedrive
- and more...



Meeting room, Conferencing and Webinar

Rainbow Webinar

- Create your webinar session directly from the Rainbow client
- Manage and add easily speakers and host
- Offer a better experience with YouTube videos in the waiting room
- Boost engagement with live polling
- Record the webinar session
- Get analytics



ALE-400, ALE-500 DeskPhones

- 3D audio broadcasting
- 360° audio capture with 3 microphones

AD52 headset

- Comfortable wireless handset for remote meetings (DECT and Bluetooth)

Rainbow Room

- Turn any room into a virtual conference room



Click for more details



On-site mobility DECT / WLAN

DECT/SIP-DECT handsets

- 8262/8262Ex** • IP65 • Industrial design
- Business features • Bluetooth • Alarms
- Lone worker protection • ATEX
- 8254** • IP65 ruggedized • Antibacterial plastics and lens
- Business features • Large color screen
- 8244** • Business features • Large color screen
- Bluetooth • Alarms • Alarm key on top
- 8234** • Business features
- 8214** • For essential functions



WLAN handsets

- Rugged design • 15 hours talk time
- 8158s** • SIP/NOE • Business features
- Color display • Alarm features
- 8168s** • Business features • SIP/NOE
- Wideband audio • Color display
- Alarm button • BTLE compatible

SIP-DECT, IP-DECT, DECT base stations

8328/8368 SIP-DECT / 8378 IP-xBS

8379 IBS DECT / 8379 IBS DECT ATEX



Click for more details

Desk phones - Softphones ALE DeskPhones

ALE DeskPhones: Enterprise

- NOE-SIP and OmniPCX Enterprise Purple (SIP)
- Symphonic HD audio • 3D soundbar
- 2xUSB-C ports • Dual Gigabit Ethernet port
- Business features • Hot-desking mode
- VPN client • Customization kits: 4 colors
- ALE-108* Bluetooth / Wi-Fi module
- ALE-100* alphabetic keyboard
- ALE-120* Color-screen key expansion module
- ALE-500** • 5.5" touch screen • 3 microphones
- Bluetooth handset option
- ALE-400** • 4.3" touch screen
- Mechanical dial pad
- 3 microphones • Bluetooth handset option
- ALE-300** • 3.5" color screen
- 10 contextual keys with LED

ALE DeskPhones: Essential

- NOE-SIP and OmniPCX Enterprise Purple (SIP)
- Wideband audio • Business features
- USB-A, USB-C ports • ALE-10* alphabetic keyboard
- EM200* color expansion module
- ALE-30/30h** • 3.5" color screen
- 10 contextual keys with LED
- Dual Gigabit Ethernet port (ALE-30)
- Hybrid digital / IP port (ALE-30h)
- ALE-20/20h** • 2.8" backlit screen
- 6 contextual keys with LED
- Dual Gigabit Ethernet port (ALE-20)
- Hybrid digital / IP port (ALE-20h)

ALE DeskPhones: Basic

- ALE-3** • 2.8" color screen • 4 contextual keys
- SIP • USB-A • Dual Gigabit Ethernet port
- ALE-2** • 2.8" backlit screen • 3 contextual keys
- SIP • Dual Gigabit Ethernet port

Click for more details

Enterprise models



* Optional

Essential models



* Optional

Basic models



IP Desktop SoftPhone

- Business telephony
- Call Centre Agent
- VoIP/LAN/Off-site (VPN)
- PC/Mac/Android

8088 Smart DeskPhone

- 7" touch screen
- Built-in video camera
- Advanced business features
- NOE-IP or SIP
- Android apps

8008G, 8008 DeskPhones

- Compact size
- Advanced telephony
- 8008G Dual Gigabit Ethernet port



ALE SoftPhone

- SIP • LAN • Off-site (SBC)
- Audio and video call
- PC • Android • iPhone



SIP phones ALE SIP DeskPhones

For third-party SIP communication systems

- OpenVPN • PoE • IPv4/IPv6
- 2 USB ports and Expansion Modules for the Myriad (M) range
- M8** • 5" color screen • BT 5.2 • Wi-Fi
- 20 SIP accounts
- M7s pro** • 3.5" color screen • BT 5.2
- Wi-Fi • 8 SIP accounts
- M7s** • 3.5" color screen
- 8 programmable keys
- M5s** • 2.8" color screen
- 8 programmable keys
- M3s** • 2.8" backlit screen • 6 programmable keys
- ALE-3** • 2.8" color screen • 4 contextual keys • USB-A
- Dual Gigabit Ethernet port
- ALE-2** • 2.8" backlit screen • 3 contextual keys • Dual Gigabit Ethernet port

Click for more details

